



QUATERNARY CHEMICAL DISINFECTION CHAMBER

ELIMINATES BACTERIA THROUGH CONVENTIONAL CHEMICAL DISINFECTION



Quaternary Cart Chamber

Product Information

- Water & Chemical Disinfection Chamber
- Standard Treatment Cycle (Dwell Required)
- Low Water Consumption (< 1gal/cart)
- Appropriate For All Cart Types
- Rugged, "Laundry-Proof" Design
- Built-in Sump or Pit Installation

- **Conventional disinfection process that delivers a hygienically clean cart**
- **Disinfects up to 30 carts per hour* (*adhere to the dwell time guidelines set by the chemical manufacturer)**
- **Over thirty years as the "industry standard" for cart disinfection**

Technical Data

- UL Listed Controls and Components
- Electric: 240/60/3 40 FLA, or 480/60/3 20 FLA
- Water: Min. 10 GPM @ 35 PSI supply (max 140°)
- Compressed Air: 1/2" NPT, 2 CFM @ 80 PSI
- Standard 1-Year Warranty
- Factory Start-Up Included
- Fully Assembled and Tested

Safety

- Fully Contained System (No Operator Exposure)
- User Adjustable Chemical Pump
- User Friendly HMI, E-Stops, Interlock Shutoff
- Easily Accessible Service Components

Construction

- Heavy Gauge Stainless Steel Build
- Insulated Dual Wall Construction
- Automatic Door Operation (Standard)
- Optional: Single Door Operation (w/out Eject)
- Optional: Roof-Mounted Blower Drying Assist

**Call for additional information or
to ask about our UV-C
disinfection options!**



800-944-1711



sales@energenics.com | energenics.com

