

# CART CHAMBERS

## Quaternary Chemical Cart Disinfection

### Features:

- Industry established cart disinfection system
- Stainless steel /insulated dual wall construction
- Built-in mechanical chamber
- HMI touchscreen control and diagnostics
- Fully adjustable cycle times
- Pass-through entry/exit doors
- PLC based, UL listed controls and components
- Over-pit drain configuration (standard)
- Easily accessible service components
- Less than 1 gallon water per cart (standard)

### Benefits:

- Effective against bacteria and viruses
- Up to 30 carts per hour productivity rate
- Accommodates all cart types
- Suitable for all chemical disinfectants
- Requires no daily adjustments
- Supports industry healthcare accreditations

### Added Options:

- Pre-wash cycle with additional pump and spray assembly
- Automated entry/exit doors
- Automated end-of-cycle cart ejection
- Built-in sump with ramps (for level floor installations)
- Forced air drying assist

DISINFECTION  
CHAMBERS



Quaternary Chamber (w/ sump, ramp, and blower)

### Utilities:

- Water
  - 1/2" NPT, 10 GPM @ 35 PSI
  - Temperature - per supplied chemical guidelines
- Compressed Air
  - 1/2" NPT, 2 CFM @ 80 PSI
  - Filtered and Dried
  - Doors: 40 psi; Cart ejection: 80 psi
- Electrical
  - 240/60/3 40 FLA, or
  - 480/60/3 20 FLA

### Disinfection:


- Requires purchased chemicals
- Dwell time -in minutes (varies per chemical manufacture guidelines)



# CART CHAMBERS

## Quaternary Chemical Cart Disinfection Chamber

### Dimensions:



**Fully Assembled & Factory Tested**

[www.energenics.com](http://www.energenics.com)